

Sodium Hydroxide Solution, 50%

SECTION 1 – CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

△	Manufacturer's name and address:	Supplier's name and address:
	<p>Olin Corporation – Chlor Alkali Products Division</p> <p>CLEVELAND, TN OFFICE 490 Stuart Road NE Cleveland, TN 37312-4918 U.S. • (423) 336-4850</p>	<p>PCI Chemicals Canada Company d/b/a Olin Chlor Alkali Products</p> <p>MONTREAL, QC OFFICE 2020 University, Suite 2190 Montreal, Quebec H3A 2A5 Canada • (514) 397-6100</p>

Product Name: Sodium Hydroxide Solution, 50%

CAS#: 1310-73-2 **Preparation date (M/D/Y):** 10/02/08

MSDS Code: NaOH(50)-E **Revision date (M/D/Y):** 05/11/2010

Synonyms: Caustic soda liquid 50%, Soda lye, Lye, Liquid Caustic, Sodium Hydrate

Product Use: Neutralizing agent, industrial cleaner, pulping and bleaching, soap manufacturing

Emergency Contacts (24 hr.)

FOR INFORMATION REGARDING ON SITE CHEMICAL EMERGENCIES INVOLVING A SPILL OR LEAK, CALL

△ **Canada: 1-800-567-7455**
U.S.: 1-800-424-9300 – CHEMTREC

SECTION 2 – COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% (w/w)	ACGIH	CAS NO.
△ Sodium Hydroxide	49 – 52	2 mg/m ³ (TLV-C)	1310-73-2

SECTION 3 – HAZARD IDENTIFICATION

Emergency Overview: Odorless, clear, non-volatile liquid. EXTREMELY CORROSIVE! Causes severe burns on contact. Can cause blindness, permanent scarring and death. Aerosols can cause lung injury – effects may be delayed. Highly reactive. Can react violently with water and numerous commonly encountered materials, generating enough heat to ignite nearby combustible materials. Contact with many organic and inorganic chemicals may cause fire or explosion. Reacts with some metals to liberate hydrogen gas, which can form explosive mixtures with air. Will not burn. Harmful to aquatic life. Read the entire MSDS for a more thorough evaluation of the hazards.

Potential Health Effects:

△ **Routes of exposure:** Inhalation, skin contact, eye contact and ingestion.

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 2 of 10

Inhalation: Sodium hydroxide does not readily form a vapor and inhalation exposure is likely to occur as an aerosol. Due to its corrosive nature, sodium hydroxide aerosols could cause pulmonary edema (severe, life-threatening lung injury). The development of pulmonary edema may be delayed up to 48 hours after exposure. The early symptoms of pulmonary edema include shortness of breath and tightness in the chest.

Skin Contact: EXTREMELY CORROSIVE! Sodium hydroxide is capable of causing severe burns with deep ulceration and permanent scarring. It can penetrate to deeper layers of skin and corrosion will continue until removed. The severity of injury depends on the concentration (solutions) and the duration of exposure. Burns may not be immediately painful; onset of pain may be delayed minutes to hours. Several human studies and case reports describe the corrosive effects of sodium hydroxide. A 4% solution of sodium hydroxide, applied to a volunteer's arm for 15 to 180 minutes, caused damage which progressed from destruction of cells of the hard outer layer of the skin within 15 minutes to total destruction of all layers of the skin in 60 minutes. Solutions as weak as 0.12% have damaged healthy skin within 1 hour.

Eye Contact: EXTREMELY CORROSIVE! The severity of injury increases with the concentration, the duration of exposure, and the speed of penetration into the eye. Damage can range from severe irritation and mild scarring to blistering, disintegration, ulceration, severe scarring and clouding. Conditions, which affect vision such as glaucoma and cataracts, are possible late developments. In severe cases, there is progressive ulceration and clouding of eye tissue which may lead to permanent blindness.

Ingestion: EXTREMELY CORROSIVE! Severe pain; burning of the mouth, throat and esophagus; vomiting; diarrhea; collapse and possible death may result.

Chronic Effects: SKIN: Repeated or prolonged skin contact would be expected to cause drying, cracking, and inflammation of the skin (dermatitis).

Existing Medical Conditions Possibly Aggravated by Exposure: Asthma, bronchitis, emphysema and other lung diseases and chronic nose, sinus or throat conditions. Skin irritation may be aggravated in individuals with existing skin disorders.

Carcinogenicity: Sodium hydroxide is not classified as a carcinogen by ACGIH (American Conference of Governmental Industrial Hygienists) or IARC (International Agency for Research on Cancer), not regulated as a carcinogen by OSHA (Occupational Safety and Health Administration), and not listed as a carcinogen by NTP (National Toxicology Program).

△ **Other important hazards:** Refer to TOXICOLOGICAL INFORMATION (Section 11) for additional information.

SECTION 4 – FIRST AID MEASURES

General: If you feel unwell, IMMEDIATELY seek medical advice (show this document).

Inhalation: Move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. Give artificial respiration ONLY if breathing has stopped. Do not use mouth-to-mouth method if victim ingested or inhaled the substance: induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Give Cardiopulmonary Resuscitation (CPR) only if there is no pulse AND no breathing. Obtain medical attention IMMEDIATELY. Symptoms of pulmonary edema can be delayed up to 48 hours after exposure.

Skin Contact: Immediately flush skin with lukewarm water for at least 20 minutes, and up to 60 minutes if necessary. Under lukewarm water remove contaminated clothing, jewelry, and shoes. If irritation persists, repeat flushing. Obtain medical attention immediately. Discard contaminated clothing and shoes in a manner which limits further exposure.

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 3 of 10

Eye Contact: Immediately flush eyes with lukewarm water for at least 20 minutes, and up to 60 minutes if necessary. Hold eyelids open during flushing. If irritation persists, repeat flushing. Obtain medical attention IMMEDIATELY. Do not transport victim until the recommended flushing period is completed unless flushing can be continued during transport.

Ingestion: DO NOT INDUCE VOMITING. If victim is alert and not convulsing, rinse mouth and give as much water as possible to dilute material (8 to 10 oz. or 240 to 300 mL). If spontaneous vomiting occurs, have victim lean forward with head down, rinse mouth and administer more water. IMMEDIATELY transport victim to an emergency facility.

SECTION 5 – FIRE FIGHTING MEASURES

Flammability	Not applicable. Not combustible (does not burn).
Flash Point (method)	Not applicable.
Flammable Limits (Lower)	Not applicable
Flammable Limits (Upper)	Not applicable
Auto Ignition Temperature	Not applicable
Combustion and Thermal Decomposition Products	Sodium oxide fumes
Rate of Burning	Not applicable
Explosive Power	Not applicable
Sensitivity to Mechanical Impact	Not sensitive ; stable material
Sensitivity to Static Charge	Not applicable

Fire and Explosion Hazards: Sodium hydroxide will not burn or support combustion. The reaction of sodium hydroxide with water and a number of commonly encountered materials (see Section 10) can generate sufficient heat to ignite nearby combustible materials. Sodium hydroxide can react with metals, such as aluminum, tin and zinc, to form flammable hydrogen gas.

Extinguishing Media: Use extinguishing media suitable for the surrounding fire. If water is used, care should be taken, since it can generate heat and cause spattering if applied directly to sodium hydroxide.

Special Information: Evacuate area and fight fire from a safe distance or a protected location. Approach fire from upwind. If possible, isolate materials not involved in the fire and protect personnel. Move containers from fire area if it can be done without risk.

Water can be used with extreme caution to extinguish a fire in an area where sodium hydroxide is stored. The water must not come into contact with the sodium hydroxide. Water can be used in flooding quantities as a spray or fog to keep fire-exposed containers cool and absorb heat. At high temperatures, fuming may occur, giving off a strong, corrosive gas. Do not enter without wearing specialized protective equipment suitable for the situation.

Evacuation: If tank or tank truck involved in a fire, ISOLATE and consider evacuation of one-half (1/2) mile (800 meters) in all directions.

Fire Fighting Protective Equipment: Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. Chemical resistant clothing (e.g. chemical splash suit) and positive pressure self-contained breathing apparatus (MSHA/NIOSH approved or equivalent) may be necessary.

NOTE: Also see "Section 10 - Stability and Reactivity"

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 4 of 10

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spills, Leaks, or Releases:

- Restrict access to area until completion of clean up. Ensure trained personnel conduct clean up. Ventilate area.
- Wear adequate personal protective equipment (See Section 8). Do not touch spilled material.
- Prevent entry into sewers or waterways.
- Land spill of sodium hydroxide: Solutions should be contained by diking with inert material, such as sand or earth. Solutions can be recovered or carefully diluted with water and cautiously neutralized with acids such as acetic acid or hydrochloric acid.
- Water spill: Neutralize with dilute acid.
- Comply with Federal, Provincial/State and local regulations on reporting releases.

Deactivating Chemicals: Weak acid solutions (acetic, hydrochloric or sulfuric acid).

Waste Disposal Methods: Dispose of waste material at an approved waste treatment/disposal facility, in accordance with applicable regulations. Do not dispose of waste with normal garbage or to sewer systems.

- Note**
- Clean-up material may be a RCRA Hazardous Waste on disposal.
 - Spills are subject to CERCLA reporting requirements: RQ = 1000 lbs. (454 kg).

SECTION 7 – HANDLING AND STORAGE

Precautions: EXTREMELY CORROSIVE! Have emergency equipment (for fires, spills, leaks, etc.) readily available. Ensure all containers are labeled. Wear appropriate Personal Protection Equipment (*Refer to Section 8*). People working with this chemical should be properly trained regarding its hazards and its safe use.

Handling Procedures and Equipment: Use smallest possible amounts in designated areas with adequate ventilation. Keep containers closed when not in use. Empty containers may contain hazardous residues. Avoid generating mists. Transfer solutions using equipment, which is corrosion-resistant. Cautiously, transfer into sturdy containers made of compatible materials. Never return contaminated material to its original container. Considerable heat is generated when diluted with water. Proper handling procedures must be followed to prevent vigorous boiling, splattering or violent eruption of the diluted solution. Never add water to a sodium hydroxide solution. **ALWAYS ADD SODIUM HYDROXIDE TO WATER** and provide agitation. When mixing with water, stir small amounts in slowly. Use cold water to prevent excessive heat generation.

Storage Requirements: Store in a cool, dry, well-ventilated area. Keep containers tightly closed when not in use and when empty. Protect from damage. Store away from incompatible materials such as strong acids, nitroaromatic, nitroparaffinic or organohalogen compounds. See Section 10 for Incompatibles. Use corrosion-resistant structural materials and lighting and ventilation systems in the storage area. Containers made of nickel alloys are preferred. Steel containers are acceptable if temperatures are not elevated. Nickel is the preferred metal for handling this product. Plastics or plastic-lined steel, or FRP tanks of Derakane vinyl ester resin may be suitable. Container contents may develop pressure after prolonged storage. Drums may need to be vented. Trained personnel should only perform venting.

Storage Temperature: Avoid freezing. Do not expose sealed containers to temperatures above 40°C (104°F).

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 5 of 10

SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

PREVENTIVE MEASURES

Recommendations listed in this section indicate the type of equipment which will provide protection against over exposure to this product. Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.

Engineering Controls: Local exhaust ventilation should be applied wherever there is an incidence of point source emissions or dispersion of regulated contaminants in the work area. Ventilation control of the contaminant as close to its point of generation is both the most economical and safest method to minimize personnel exposure to airborne contaminants. The most effective measures are the total enclosure of processes and the mechanization of handling procedures to prevent all personal contact.

PERSONAL PROTECTIVE EQUIPMENT

Maintain eye wash fountain and quick-drench facilities in work area. Detailed requirements for personal protective equipment should be established on a site-specific basis.

Eye Protection: Wear full face-shield and chemical safety goggles when there is potential for contact.

Skin Protection: Wear appropriate personal protective clothing to prevent skin contact.

Guidelines for sodium hydroxide solutions, 30-70%:

RECOMMENDED (resistance to breakthrough longer than 8 hours): Butyl rubber; natural rubber, neoprene rubber, nitrile rubber, polyethylene, polyvinyl chloride, Teflon™, Viton™, Saranex™, 4H™, Barricade™, CPF 3™, Responder™, Trelchem HPS™, Tychem 10000™.

NOT RECOMMENDED for use (resistance to breakthrough less than 1 hour): Polyvinyl alcohol.

Respiratory Protection:

Up to 10 mg/m³: Supplied Air Respirator (SAR) operated in a continuous-flow mode, eye protection needed; or full face-piece respirator with high-efficiency particulate filter(s); or powered air-purifying respirator with dust and mist filter(s), eye protection needed; or full face-piece Self-Contained Breathing Apparatus (SCBA); or full face-piece SAR.

Emergency or Planned Entry into Unknown Concentrations or IDLH Conditions: Positive pressure, full face-piece SAR; or positive pressure, full face-piece SAR with an auxiliary positive pressure SAR.

ESCAPE: Full face-piece respirator with high-efficiency particulate filter(s); or escape-type SCBA.

EXPOSURE GUIDELINES

PRODUCT: Sodium hydroxide:

	ACGIH Ceiling Exposure Limit (TLV-C)	2 mg/m ³
Δ	OSHA PEL-TWA	2 mg/m ³
	NIOSH IDLH	10 mg/m ³
	NIOSH REL:	C 2 mg/m ³

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 6 of 10

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Alternate Name(s)	Caustic soda liquid 50%, Soda lye, Lye, Liquid Caustic, Sodium Hydrate
Chemical Name	Sodium hydroxide
Chemical Family	Alkali hydroxide
Molecular Formula	NaOH
Molecular Weight	40.01
Physical State and Appearance	Clear-to-slightly turbid liquid
Odor	Odorless
pH	14.0 (Aqueous solution: 5%)
Vapor Pressure	0.2 kPa (1.5 mm Hg) at 20 °C (68°F) (50% solution)
Vapor Density (Air = 1)	Not applicable
Boiling Point	140 °C (284 °F) (50% solution)
Freezing Point	12 °C (53.6 °F) (50% solution)
Solubility (Water)	Soluble in all proportions
Specific Gravity	1.53 (50% solution) 15.5 °C (60°F)
Evaporation Rate	Not applicable
Viscosity (cp):	78.3 at 20 °C (68°F)
Bulk Density (lbs/cu ft):	95.5
Coefficient of Oil/Water Distribution	Essentially zero

SECTION 10 – STABILITY AND REACTIVITY

Chemical Stability: Stable at room temperature.

Hazardous Decomposition Products: Thermal decomposition: sodium oxide fumes

Conditions to Avoid: Water. Keep away from incompatibles.

Incompatibility with other Substances: Sodium hydroxide reacts vigorously, violently or explosively with many organic and inorganic chemicals, such as strong acids, nitroaromatic, nitroparaffin and organohalogen compounds, glycols and organic peroxides. Reacts violently with water generating significant heat and dangerously spattering corrosive sodium hydroxide. Violently polymerizes acetaldehyde, acrolein or acrylonitrile. Produces flammable and explosive hydrogen gas if it reacts with sodium tetrahydroborate or certain metals such as aluminum, tin, or zinc. Can form spontaneously flammable chemicals upon contact with 1,2- dichloroethylene, trichloroethylene or tetrachloroethane. Can produce carbon monoxide upon contact with solutions of sugars, such as fructose, lactose and maltose.

Corrosivity to Metals: Corrosive to aluminum, tin, zinc, copper, and most alloys in which they are present including brass and bronze. Corrosive to steel at elevated temperatures above 40°C(104°F).

Stability and Reactivity Comments: Slowly attacks glass at room temperature.

Hazardous Polymerization: Will not occur. However, it can induce hazardous polymerization of acetaldehyde, acrolein, and acrylonitrile.

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 7 of 10

SECTION 11 – TOXICOLOGICAL INFORMATION

For more toxicological information, refer to Section 3.

TOXICOLOGICAL DATA:

Toxicological Data: Sodium hydroxide

Toxicity data: LDLo - Lowest published lethal dose oral rabbit 500 mg /kg ;
LD₅₀ intraperitoneal mouse 40 mg/kg

Irritation data: Standard Draize Tests: 500 mg/24 hour(s) skin-rabbit severe;
400 µg eyes-rabbit mild; 1 percent eyes-rabbit severe;

Mutagenicity: There is no evidence of mutagenic potential.

Reproductive Effects: No information is available.

Teratogenicity and Fetotoxicity: No information is available.

Synergistic Materials: No information is available.

Skin and Respiratory Sensitization: No information is available.

Irritancy: Strong eye and skin irritant.

SECTION 12 – ECOLOGICAL INFORMATION

Ecotoxicological Information:

LC₁₀₀ Cyprinus Carpio 180 ppm/24 hr @ 25°C (77°F)

TLm mosquito fish 125 ppm/96 hr (fresh water);

TLm Bluegill 99 mg/L/48 hr (tap water)

Persistence and Degradation: Degrades readily by reacting with natural carbon dioxide in the air. Does not bioaccumulate.

SECTION 13 – DISPOSAL CONSIDERATIONS

Review federal, state and local government requirements prior to disposal.

Do not dispose of waste with normal garbage, or to sewer systems.

Whatever cannot be saved for recovery or recycling, including containers, should be managed in an appropriate and approved waste disposal facility. Processing, use or contamination of this product may change the waste management options.

RCRA: Test waste material for corrosivity, D002, prior to disposal.

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 8 of 10

SECTION 14 – TRANSPORT INFORMATION

	TDG	DOT
Shipping Name	SODIUM HYDROXIDE, SOLUTION	Sodium hydroxide, solution
Hazard Class/Division	8	8
Identification No.	UN1824	UN1824
Packing Group:	II	II
Reportable Quantity	Not Applicable	RQ: 1000 lbs. (454 kg)
ERAP	NONE	Not Applicable

- Δ **IATA/ICAO Shipping Description:** UN1824, Sodium hydroxide solution, Class 8, PG II is accepted for air transport.
- Δ **For Chemical Emergencies in Transportation Requiring Activation of Olin 24 Hour Emergency Response Plan Call:**

U.S. 1-800-424-9300 – Chemtrec
Canada 1-800-567-7455

SECTION 15 – REGULATORY INFORMATION

Δ **CANADIAN INFORMATION:**

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and this MSDS (Material Safety Data Sheet) contains all the information required by the CPR.

Controlled Products Regulations (WHMIS) Classification:

E: Corrosive Material

CEPA / Canadian Domestic Substances List (DSL): Y

WHMIS Ingredient Disclosure List: Meets criteria for disclosure at 1% or greater.

Δ **USA INFORMATION:**

OSHA Classification: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

SARA Regulations sections 313 and 40 CFR 372: N

SARA Hazard Categories, SARA SECTIONS 311/312 (40 CFR 370.2):

ACUTE: Y

CHRONIC: N

FIRE: N

REACTIVE: Y

SUDDEN RELEASE: N

OSHA PROCESS SAFETY (29 CFR 1910.119): N

CERCLA SECTION 103 (40 CFR 302.4): Y

Reportable Quantity (RQ) under CERCLA: 1000 lbs. (454 kg)

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 9 of 10

TSCA Inventory Status: Y

This product does not contain nor is it manufactured with ozone depleting substances.

△ EUROPEAN ECONOMIC COMMUNITY (EEC) INFORMATION:

EINECS Number: 215-185-5

CALIFORNIA PROP 65 COMPONENTS:

This product is not listed, but it may contain elements known to the State of California to cause cancer or reproductive toxicity as listed under Proposition 65 State Drinking Water and Toxic Enforcement Act. For additional information, contact Olin Technical Services (800-299-6546)

SECTION 16 – OTHER INFORMATION

- △ The information contained herein is offered only as a guide to the handling of this specific material and has been prepared in good faith by technically knowledgeable personnel. It is not intended to be all-inclusive and the manner and conditions of use and handling may involve other and additional considerations. No warranty of any kind is given or implied and Olin will not be liable for any damages, losses, injuries or consequential damages that may result from the use of or reliance on any information contained herein. This Material Safety Data Sheet is valid for three years.

Revision Indicators:

- △ In the left margin indicates a revision or addition of information since the previous issue.

**National Fire Protection Association (NFPA) Rating
Hazardous Materials Identification System (HMIS) Rating**

	NFPA	HMIS	
HEALTH	3	3	4 = Extreme/Severe
FIRE	0	0	3 = High/Serious
REACTIVITY / INSTABILITY	1	1	2 = Moderate
SPECIAL HAZARDS	N/Ap	N/Ap	1 = Slight
			0 = Minimum
			W = Water Reactive
			OX = Oxidizer
			* = Chronic health hazard

△ REFERENCES:

1. Chemlist, STN Database, Chemical Abstract Service, 1999
2. "CHEMINFO", CCOHS, Canadian Centre for Occupational Health and Safety, Hamilton, Ontario, Canada, (2008).
3. DOSE, Royal Society of Chemistry, Aug 27, 1999.
4. HSDB- Hazardous Substances Data Bank, CCOHS, 2008.
5. RTECS-Registry of Toxic Effects of Chemical Substances, On-line search, Canadian Centre for Occupational Health and Safety RTECS database, Doris V. Sweet, Ed., National Institute for Occupational Safety and Health, U.S. Dept. of Health and Human Services, Cincinnati, Entry Update/ August 2007.
6. "2008 Threshold Limit Values and Biological Exposure Indices", American Conference of Government Industrial Hygienists, 2008.
7. Merck, 11th Edition, 1989

SODIUM HYDROXIDE SOLUTION, 50%

Update/Review: May 11, 2010

Page 10 of 10

Δ LEGEND:

ACGIH	- American Conference of Governmental Industrial Hygienists
AFFF	- Aqueous Film Forming Foam
AIHA	- American Industrial Hygiene Association
CAS #	- Chemical Abstracts Service Registry Number
CERCLA	- Comprehensive Environmental Response, Compensation, and Liability Act
CFR	- Code of Federal Regulations
DOT	- Department of Transportation
EINECS	- European Inventory of Existing Chemical Substances
EPA	- Environmental Protection Agency
ERAP	- Emergency Response Assistance Plan
IATA	- International Air Transportation Association
ICAO	- International Civil Aviation Organization
FRP	- Fiberglass Reinforced Plastic
HMIS	- Hazardous Materials Identification System
IARC	- International Agency for Research on Cancer
IDLH	- Immediately Dangerous to Life and Health
LC50	- The concentration of material in air expected to kill 50% of a group of test animals
LD ₅₀	- Lethal Dose expected to kill 50% of a group of test animals
MSHA	- Mine Safety and Health Administration
N/Ap	- Not Applicable
N/Av	- Not Available
NFPA	- National Fire Protection Association
NIOSH	- National Institute for Occupational Safety and Health
NTP	- National Toxicology Program
OSHA	- Occupational Safety & Health Administration
PEL	- Permissible Exposure Limit
PVC	- Polyvinyl chloride
RCRA	- Resource Conservation and Recovery Act
SARA	- Superfund Amendments and Reauthorization Act of the U.S. EPA
STEL	- Short Term Exposure Limit
TDG	- Transportation of Dangerous Goods Act/Regulations
TLV	- Threshold Limit Value
TSCA	- Toxic Substances Control Act
TWA	- Time Weighted Average
WEEL	- Workplace Environmental Exposure Level
WHMIS	- Workplace Hazardous Materials Identification System